



E25

GAS INSERT



Designed & Built in
North America



Insert Specifications

BTU Maximum Input - NG	28,000 BTU		
BTU Minimum Output*	14,000 BTU		
Heating Area	1,600 ft ²		
P4 Efficiency	TBA		
Glass Size	420 in ²		
Minimum Install Dims. †	HEIGHT 19 ⁷ / ₈ "	WIDTH 27 ⁷ / ₈ "	DEPTH 13"

* Turn down is based on a 50% valve.

† Based on installation with the Slim Surround. Depth can vary by panel.

Design Features

- SIT Valve 820 (Standing Pilot)
- SIT Valve 885 (IPI System with Remote)
- Glass Size: 26¹/₄" x 16", 420 in²
- Included Traditional Log Set
- Easy Access Burner Switch (NOVA)
- Stainless Steel Burner
- Steel Firebox Grate
- Enviro's Smallest Install Depth - Only 13"
- Limited Lifetime Warranty

Gas Insert Options

- Hearth Riser
- Traditional Log Set - Included
- Liner Options:
 - Painted Liner - Included
 - Brick Liner
- Surround Options:
 - Surround Panel - Included 25³/₄" x 39"
 - Trimmable Panel 30.2" x 48"
- Optional 110 CFM Fan (with variable control)

Price: