

ENVIRO
FIREPLACES

INTRODUCING THE

IRONWOOD
STEEL HYBRID WOOD INSERT

Why choose between **flame** and **efficiency** when you can **have both** with our new **hybrid technology**?

DESIGN FEATURES

- True hybrid catalytic
- Large fire viewing area
- 2 wood handles walnut or black
- Front-mounted air adjustment
- Catalytic bypass adjustment
- Air wash curtain
- Cast iron doors
- 150CFM Variable speed blower
- 120° fan sensor
- Secondary air tubes
- Heavy steel construction
- EPA certified
- 11 year, 100% coverage - original catalyst

OPTIONS

- Modern cast door
- Arched cast door
- Base Shelf
- Standard surround
- Oversize surround

SPECIFICATIONS

Maximum BTU Output*	80,000 BTU's		
Heating Area sq. ft. **	1,500 to 2,200		
EPA Efficiency	77%		
EPA Tested Emissions	1.77 g per hour		
Burn Time*	up to 15 hours		
Maximum Log Size	18"		
Firebox Size	2.0 cu. ft.		
Flue Size	6"		
Min. Install Dimensions †	Height 20 1/2"	Width 28 1/4"	Depth 14"

* Varies depending on floor plan, house layout, heat loss of the house and quality/moisture content of wood.

** Length of burn time tested using seasoned hardwoods.

† See owners manual for most up to date specifications.

learn more at **enviro.com**